



LITTLE BEAVER®
EARTH DRILLS & AUGERS

HYDRAULIC EARTH DRILL





HYDRAULIC EARTH DRILL

Little Beaver Hydraulic Earth Drills combine higher horsepower engines with the reversibility, reliability and convenience of hydraulic drive.

Like our Mechanical Earth Drills, these drills feature our innovative torque tube for safe one-man drilling. They offer more torque for handling tough projects.

Ideal applications:

- Sign Installation
- Mobile Home Anchoring
- Utility Anchoring
- Soil Sampling

FEATURES & BENEFITS



ENHANCED SAFETY

- Steel torque tube
- Hydraulic pressure relief valve



CONVENIENT HANDLES

- Self-centering control valve for return to neutral
- Three options to match the application



INCREASED VERSATILITY

- Simple snap-on augers
- Auger diameters ranging from 1.5 to 16 inches



EASY MANEUVERABILITY

- Easy-to-handle three-wheeled chassis
- Pneumatic wheels



SIMPLE OPERATION

- One-touch control
- Forward and reverse drive



OPTIONAL ATTACHMENTS

- Available anchoring adapters
- Additional kits for soil sampling

HYDRAULIC AUGER DRIVE HANDLE SPECIFICATIONS

| ONE-MAN HANDLE | HYD-1MH125 | | HYD-1MH150 | | HYD-1MH220 | |
|----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| TWO-MAN HANDLE | HYD-2MH125 | | HYD-2MH150 | | HYD-2MH220 | |
| Power Source | SPEED (RPM) | TORQUE (FT*LBS) | SPEED (RPM) | TORQUE (FT*LBS) | SPEED (RPM) | TORQUE (FT*LBS) |
| HYD-PS11H | 125 | 295 | 150 | 225 | 220 | 170 |
| HYD-PS13H | 125 | 295 | 150 | 225 | 220 | 170 |

HYDRAULIC ANCHOR DRIVE HANDLE SPECIFICATIONS

| MOBILE HOME ANCHORS: HYD-AH60 | | | UTILITY ANCHORS: HYD-AHE | |
|-------------------------------|-------------|-----------------|--------------------------|-----------------|
| Power Source | SPEED (RPM) | TORQUE (FT*LBS) | SPEED (RPM) | TORQUE (FT*LBS) |
| HYD-PS11H | 60 | 380 | 55 | 575 |
| HYD-PS13H | 60 | 380 | 55 | 575 |

HYDRAULIC POWER UNIT SPECIFICATIONS

| | | HYD-PS11H | HYD-PS13H |
|---------------------|-----------------------------|--------------------------|--------------------------|
| ENGINE | Brand/Model | Honda GX340 | Honda GX390 |
| | Power @ 3600 rpm | 10.7 hp (8.0 KW) net | 11.7 hp (8.7 KW) net |
| | Torque | 19.5 lb-ft (26.4 Nm) net | 19.5 lb-ft (26.5 Nm) net |
| | Fuel Tank Capacity (US gal) | 1.6 | 1.6 |
| | Oil Alert System | Standard | Standard |
| | Starting | Recoil | Recoil |
| HYDRAULICS | Maximum Flow (gpm) | 7 | 7 |
| | Forward/Reverse | Standard | Standard |
| | Auger Speed (rpm) | 60 to 235 | 60 to 235 |
| | Auger Torque (ft*lbs) | 170 to 380 | 170 to 380 |
| | Hydraulic Pressure (psi) | 2700 | 2700 |
| | Reservoir Capacity (US gal) | 5 | 5 |
| | Return Filter (micron) | 10 | 10 |
| | Inlet Suction Strainer | 100 US Mesh | 100 US Mesh |
| | Oil Level Indicator | Sight Gauge | Sight Gauge |
| SIZE WITH WHEEL KIT | Length (In) | 47 | 47 |
| | Width (In) | 24 | 24 |
| | Height (In) | 24 | 24 |
| | Dry Weight (Lbs) | 205 | 205 |



**VIEW ADDITIONAL PRODUCT INFORMATION,
RESOURCES AND TIPS ONLINE.**

www.YouTube.com/LittleBeaverInc



LITTLE BEAVER®
EARTH DRILLS & AUGERS
www.littlebeaver.com

Little Beaver
2009 South Houston Ave.
Livingston, TX 77351

Phone: 800-227-7515
Email: sales@littlebeaver.com
Fax: 936-327-4025